



## Specialist CPF=30<sup>A</sup>

### Special Purpose Hypertonic Arterial Fluid with Entrone

Specialist is a hypertonic formaldehyde arterial fluid suitable for use in extreme situations requiring thorough preservation and definite firmness with a maximum dehydration effect. Difficult cases such as edema, dropsy, swollen bodies, or advanced decomposition respond well to Specialist. Special buffers and hypertonic penetrating agents make it possible to obtain maximum tissue fixation and fluid distribution with enhanced drainage. The hypertonic agents present in Specialist reduce the amount of tissue moisture in the body to the maximum extent possible. Specialist should never be used for normal cases.

PH-A <sup>1</sup>	TRI-SAN <sup>2</sup>	SPECIALIST <sup>B</sup> DEFINITE <sup>3</sup> FIRMNESS	TRI-SAN <sup>4</sup> ADD FOR EXTRA FIRMNESS
1-2	1-2	10-12	2-4
→ →	MIX IN THIS ORDER		→ →

#### Notes:

- A - A value assigned to all Champion fluids ranking them on the basis of preservative ability using recommended dilutions in normal cases. The Champion Preservative Factor is not index but can equal it in certain fluids. It is derived from the total chemical composition of each fluid and results of extensive field research. The Champion Preservative Factor can be used by the embalmer to predict the reactivity, preservative value and firming action of Champion fluids.
- B - Add Champion Coloro Dyes as needed to achieve desired cosmetic effect.
  - 1 - For proper water conditioning and pH balance to maximize fluid efficiency.
  - 2 - For sanitizing action in solution and improved fluid action in all non-glutaraldehyde based fluids.
  - 3 - Embalmer should adjust quantity used according to severity of case and fluid action required. For tissue gas use at maximum rate of 16 oz.
  - 4 - For increased aldehyde action with improved preservation and sanitation. In cases of tissue gas use at rate of 8 oz. Tri-San per gallon.

**BEFORE USING, READ MATERIAL SAFETY DATA SHEET.  
FOR PROFESSIONAL EMBALMING USE ONLY.**

# MATERIAL SAFETY DATA SHEET

THE CHAMPION COMPANY  
400 Harrison Street  
Springfield, Ohio 45505  
EMERGENCY TELEPHONE NO. (937) 324-5681  
CHEMTREC: (800) 424-9300 (Spill, Leak, Fire, Exposure or Accident)

HAZARD RATING  
Health 2  
Fire 2  
Reactivity 0  
Special 0

## I. PRODUCT INFORMATION

General Type: Embalming Fluid  
Trade Name: Specialist

## II. HAZARDOUS INGREDIENTS

<u>MATERIAL (CAS)</u>	<u>%</u>	<u>OSHA PEL</u> <u>TWA/STEL (15)</u>	<u>ACGIH TLV</u> <u>TWA/STEL (15)</u>
Formaldehyde (50-00-0)	30	.75ppm/2ppm	.3ppm (ceiling)
Possible Carcinogen: NTP, IARC			
Methanol (67-56-1)	7	200ppm/NONE	200ppm/250ppm

## III. PHYSICAL DATA

Boiling Point	192° +	Freezing Point	N/A
Specific Gravity	1.080	Vapor Pressure	UNKNOWN
Vapor Density	1	Solubility in Water	COMPLETE
Percent Volatiles	7.0	Evaporation Rate	1 (Butyl Acetate = 1)
Appearance and Odor	Reddish-orange, clear solution with strong odor.		

## IV. FIRE AND EXPLOSION HAZARD DATA

Flash Point	180° F (COC) Combustible Liquid
Flammable Limits In Air	Lower 6.7 Upper 72
Extinguishing Media	Foam, Dry Chemical, Carbon Dioxide, Water Spray
Special Fire Fighting Procedures	Wear self-contained breathing apparatus, cool container with water spray.
Unusual Fire and Explosion Hazard	-----

## V. HEALTH HAZARD DATA

Threshold Limit Value	See Part II
Effects of Overexposure	If swallowed may cause burns, nausea, vomiting, diarrhea, blindness or death. Skin contact may cause burns, dermatitis or serious skin injury. Eye contact may cause burns, inflammation, eye injury or blindness. Inhalation may cause burning of throat and lungs, difficult breathing and collapse, liver damage, nerve damage or blindness. Can be absorbed through skin.
Emergency and First Aid Procedures	Contact physician immediately. If swallowed give milk or water and induce vomiting by sticking finger down throat and get medical attention. If unconscious - give nothing. If eye or skin contact - flush with water for 15 minutes. Remove contaminated clothing, get medical attention. If inhaled - remove to fresh air, give artificial respiration if not breathing, get medical attention.

---

---

## VI. REACTIVITY DATA

Stability	Product is stable
Conditions to Avoid	Sparks, heat and open flames
Incompatibilities	Strong acids and alkalis
Hazardous Decomposition Products	At high temperatures may release carbon monoxide or carbon dioxide
Hazardous Polymerization	Will not occur

---

---

## VII. SPILL OR LEAK PROCEDURES

If Material is Spilled	Neutralize with sodium sulfite solution and flush to sewer with large quantity of water - if allowed. Mop up with dry, non-reactive absorbent and dispose of as solid waste as allowed.
Waste Disposal Method	Flush to chemical sewer, incinerate, dispose in sanitary landfill - if allowed or flush to waste treatment system - if allowed.

---

---

## VIII. SPECIAL PROTECTION INFORMATION

Respiratory Protection	Unnecessary if area is adequately ventilated - use organic vapor mask if necessary.
Local Ventilation	Preferred
Mechanical Ventilation	Acceptable if necessary
Special Ventilation	Not normally required
Other Ventilation	Not normally required
Protective Gloves	Impervious vinyl or rubber type
Eye Protection	Coverall goggles or full face shield
Other Protective Equipment	Safety shower, eye wash and full protective clothing is required.

---

---

## IX. SPECIAL PRECAUTIONS

Maintain adequate ventilation and engineering controls to insure exposure levels below OSHA limits. Avoid prolonged inhalation or contact with skin or eyes.

Keep bottles tightly capped. Keep away from heat and flames. Store in cool, dry, well-ventilated area.

---

---

The information herein given is in good faith but no warranty, expressed or implied, is made, except that to the best of the Company's knowledge it is accurate. The Champion Company does not assume any legal responsibilities for use or dependence upon same. Customers may wish to conduct tests of their own. The user is urged to read the information provided on the label before using product.

Specialist

Date July 2004

---

---